



IGPE
INNOVATIVE GLOBAL PRODUCTS EUROPE

YOUR SAFETY MATTERS

PRO-BARRIER

Flood Protection and Defense Barriers


PRO3 Barrier – Assembly



1 PRO3 barriers come flat-packed and are erected by simply placing units at the location and standing them upright and pulling open.



2 These units are simply extended by placing the joining pins between the two coils.



3 Before filling units, YOU MUST ensure that the bottom flap is tucked underneath the units to create a seal.

This is especially important for a flood barrier.



4 When starting to fill, place 200 mm of fill at each end of your wall. Level manually and pack by foot. Continue this process evenly along the barriers until all units are filled to the top and are fully compacted.



X-Kit

The PRO-BARRIER can be lifted and relocated using the X-Kit. The X-Kit is a special tool for safe uninstallation and emptying of PRO-BARRIER. This is, in fact, the most useful form of recycling as the entire product can be re-used in another location, possibly for another purpose.

PALLET / TRANSPORT INFORMATION *

Unit PRO3 **	Units Per Pallet	Total Length	Height	Width	Length	Weight
5 x 1 x 1 m	20	100 m	1,80 m	1,15 m	1,15 m	1.130 kg

* Pallets not stackable ** Unit – 5 joined cells



+420 739 672 339

